



Unifast–Prime Quick-Drying

Product Descriptions: -A quick drying primer with the advantage of zinc phosphate based on fast drying synthetic resin.

Intended Uses: - Suitable for steel structure sheet metal etc.
The product is recommended for new structure as well as maintenance finish also.

Product Information: -Colours	Grey, Off White, Black & Red oxide
Finish/Sheen	Matt
Volume Solids	54% (May Vary as per shade)
Typical Film Thickness	30-40 microns dry
Theoretical Coverage	11 (m ² /lt) at 35 microns dft.
Practical Coverage	Allow appropriate loss factor.
Method of Application	Spray, Brush, Roller

Dying Information: - 30°C

Touch dry : -	10 minute
Tack Free : -	2 Hours
Hard Dry : -	Over night
Pot Life : -	Not applicable



Unifast–Prime Quick-Drying

Direction for use (For Air Spray)

1. Ensure the surface to be painted is free from any loose paint, dust or grease
 2. Stir well the paint thoroughly in the container.
 3. Adjust the viscosity 20-22 Sec. Mix the thinner with paint as per recommended ratio (i.e.; 25% by volume) for spraying.
 4. Stain the paint with bloating nylon no. 20.
 5. Apply two coats of the primer on the surface.
 6. Keep the pressure to 2.8 - 3.5 kg / sq. cm. & air should be completely dry and free from moisture.
-

Warning: -

Flammable liquid and vapor
Cause: - Eye irritation
May cause skin irritation

First aid: -

- 1. For Eyes:** - 1. Immediately flush with plenty of water
2. Get medical attention
3. Remove affected cloths
- 2. On Skin:** - 1. Immediately flush with plenty of water
2. Remove contaminated clothing.
3. Wash clothing before using.
-

Handling: -

Keep away from heat, sparks and flame.
Avoid contact with eyes, skin and clothing.

Storage: -

Keep in a cool, dry and ventilated place.
Stable under normal condition.

Precautions: -

Do not add any thinner or material in paint, which is not recommended